

- **Features:**
- Withstand 470VAC Continuous
- High reliability
- User- Friendly LED indications.
- Fixed trip delays.
- Fixed trip setting for Under voltage / Over voltage
- Compact Size.



SPECIFICATION

MODEL	1P - OVP 3KVA	1P - OVP 6KVA	1P - OVP 10KVA
Input Voltage Range	150 VAC - 470 VAC		
Input Frequency	45Hz - 55Hz		
Output Voltage	165VAC - 275VAC		
Output VA	3KVA	6KVA	10KVA
Under Voltage Cut - off	165VAC		
Over Voltage Cut - off	275VAC		
Hysterises for Cut - off	5 to 10 VAC		
Cut-off VoltageTolerance	+ / - 2%		
Response Time	< 20 mSec	< 30 mSec	
Output On Delay Time after cut-off/ Start Up	4 - 8 Sec.		
LED Indication	Green=Output On, Yellow= Delay, Red= Under Cut-off / Over Cut-off		
Operating Temp	0 to 60 deg C.		
Connectivity	Input	16A 3 pin Mains Cord With 3 Pin Top, Length= 1800mm (Standard)	5 pin Terminal block 800V / 57A; Wire Size = 1.5 to 10mm ²
	Output	Screw Less 3 Pin Terminal Block 15 A	
Dimension	148*75*77	200*92*91	

Note: The Under voltage cut-off and Over voltage cut-off settings can be available as per the customer requirement.

Nuteck Products, 115 / 5 , Ramtekdi Industrial Area, Hadapsar, Pune - 411 013.

Tel: +91 20 26811161/62, F: +91 20 26811163 Email : nuteck2@gmail.com

Web : www.nuteckproducts.com www.batterychargerindia.com